

	Front	Rear
No. of wheel cylinders	2 per caliper	2
Bore of wheel cylinders	2 x 23 m.m.	22-20 m.m.
Inside diameter of brake drums	- m.m.	230 m.m.
No. of shoes per brake	-	2
Outside diameter of brake discs	280 m.m.	- m.m.
No. of pads per brake	2	-
Dimensions of brake linings per shoe or pad (if all shoes or pads in each brake are not of same dimensions, specify each)		

	Front	Rear
Length	pad top 70 m.m.	217 m.m.
	" base 45 m.m.	- m.m.
Width	48 m.m.	44 m.m.
Total area per brake	5568 m.m. ²	18100 m.m. ²

SUSPENSION

	Front	Rear
Type	ind. vertical coil	1/2 elliptic
Type of spring	Coil	Leaf
Is stabiliser fitted?	No	No
Type of shock absorber	Hydraulic	Hydraulic
No. of shock absorbers	2	2

STEERING

Type of steering gear	Cam gear
Turning circle of car	95 m., approx.
No. of turns of steering wheel from lock to lock	2 1/4

CAPACITIES AND DIMENSIONS

Fuel tank	45 litres	Sump	6.3 litres
Radiator	10 litres		
Overall length of car	368 cm.	Overall width of car	139 cm.
Overall height of car, unladen (with hood up, if appropriate)	120 cm.		
Distance from floor to top of windscreen:			
Highest point	96 cm.	Lowest point	93 cm.
Width of windscreen:			
Maximum width	105 cm.	Minimum width	99 cm.
Interior width of car	112 cm.		
No. of seats	2		
Track - Front	124 cm.	Rear	126 cm.
Wheelbase	244 cm.	Ground clearance	152 m.m.
*(To be measured at the immediate rear of the steering wheel, and the width quoted to be maintained in a vertical plane of not less than 25 cms.)			
Overall weight with water, oil and spare wheel, but without fuel	760 kgs.		

